

# CORDFLEX



## APLICAÇÃO

Mangueira para descarga de água e ar em aplicações pesadas da indústria em geral, apesar de robusta, é flexível e de fácil manuseio.



## TERMINAIS



R



BA



TPRM



TPF



TPGF



TPEM

## 75 PSI



1/2"



7/8"



20



0,44



N/A



156

1"

1 5/8"

20

0,88

N/A

300

2"

2 5/8"

20

1,57

N/A

612

3"

3 5/8"

20

2,52

N/A

912

4"

4 3/4"

20

4,12

N/A

1212

5"

5 7/8"

20

5,08

N/A

1524

6"

6 7/8"

20

6,57

N/A

1824

8"

8 7/8"

20

8,61

N/A

2436

## 150 PSI

1/2"

1 1/8"

20

0,54

N/A

156

1"

1 5/8"

20

0,88

N/A

300

2"

2 7/8"

20

2,22

N/A

612

3"

3 3/4"

20

3,16

N/A

912

4"

4 7/8"

20

4,93

N/A

1212

5"

5 7/8"

20

5,90

N/A

1524

6"

6 7/8"

20

8,10

N/A

1824

8"

9 1/8"

20

12,37

N/A

2436

## 300 PSI

1/2"

1 1/4"

20

0,73

N/A

156

1"

1 3/4"

20

1,16

N/A

300

2"

2 7/8"

20

2,60

N/A

612

3"

3 7/8"

20

4,00

N/A

912

4"

4 7/8"

20

5,76

N/A

1212

5"

6 1/8"

20

7,55

N/A

1524

6"

7 1/4"

20

10,25

N/A

1824

8"

9 5/8"

20

18,55

N/A

2436

